

Mifare® Ethernet RFID Reader

It is especially suitable for applications such as access control, time attendance, guest registration, authorization identification and identity authentication. The Mifare Ethernet RFID reader provides a read range of up to 7 cm.

Output interface is Ethernet and relay period time is configurable. The RFID reader can also be designated with a reader ID number for multi-unit communication. Internal LED and buzzer are also configurable.



Key features:

- Ethernet interface with PoE option
- Built-in relay control
- Reads MIFARE® cards
- Configurable LED and buzzer
- Compact size
- Weather resistant indoor/outdoor design
- Reader ID for multi-unit communication

Indoor/outdoor Design	Weather resistant.
Interface	Ethernet
LED/Buzzer	Internal LED and buzzer are configurable.
Multi-Applications	Supports MIFARE UID, Sector Data or MAD format with user-defined sector number.
Multi-Readers	Can be set with a Reader ID number for multi-unit communication
Certification	CE / FCC
Door control	Set built-in relay period time to open the door.

Specifications:

Model No.	ER750 / ER750A	ER755 / ER755A
Interface	Ethernet (Via CAT-5 / CAT-6)	
Applications	MIFARE UID Only	MIFARE Sector Data or MAD
Power Requirements	DC 9 V~24 V /125mA@12V ※A regulated power is recommended	
Card type	MIFARE® Classic(1K / 4K /8K)	
Maximum reading distance	Mifare(4 Byte):Up to 7 cm (MFA01A); Mifare(7 Byte):Up to 4 cm	
Frequency	13.56 MHz standard	
Audio / Visual Indication	Internal LED and Buzzer	
Relay	Built-in Relay (5A 120VAC or 5A 24VDC)	
Dimensions	112.3 L x 96W x 22D mm	
Housing material	ABS housing	
Environment	Operating temperature 0 °C ~ +60 °C ; Operating relative humidity 10~90%	
Certification	CE / FCC	

* Specification is subject to change without notice.

Applications:

- Access Control System
- Time attendance
- Guest registration system
- Authorization Identification
- Identity Authentication

Ordering Information:

- ER750-00 UID Reader, without PoE
- ER750A-10 UID Reader, with PoE
- ER755-00 UID & Sector Reader, without PoE
- ER755A-10 UID & Sector Reader, with PoE

GIGA-TMS INC.

8F, NO. 31, LANE 169, KANG-NING STREET,
HSI-CHIH DIST, NEW TAIPEI CITY, TAIWAN
Tel: 886-2-26954214 Fax: 886-2-26954213
<http://www.gigatms.com.tw/>
Email: promag@gigatms.com.tw
promag@ms24.hinet.net