



INTRODUCTION

MP600 是集佳公司針對各種應用場所設計出的多界面,多種組合,不需要驅動且內建天線的 125KHZ EM + 13.56MHZ NFC 讀寫卡機

MP600 支援工業應用所需的 R485 以及 RS232 界面,可以直接與各種設備連接. MP600 也新增支援最流行 plug-and-play USB HID, CCID 以及 PC/SC,可以在不同作業系統,如 Windows & Linux & Android ...ETC. 使用

MP600 支援坊間13.56-MHz 所有的ISO標準, 如ISO14443 Type A, Type B, and Smartlabel ISO15693.外.

The MP600 在5V 供電下提供了 低功耗工作0.9mA 以及一般工作模式200mA 交叉使用 以達到節能省電.

The MP600 提供專屬開發套件以及 DLL 讓用戶可以使用不同開發軟體 (VB .NET, C#...etc)進行開發來符合不同應用市場

應用:

- 電動車 RFID 感應 KEYLESS
- 門禁系統管理
- 系統管理者/使用者的驗證
- 出席時序管理
- 預先支付
- 票務管理
- 停車場預付/餐券管理
- 電子錢包查詢與加值
- 住家門禁系統安全應用
- 綜合應用：貨物追蹤、零售業、顧客忠誠度、博弈相關
- FIDO Support for USB Interface
- PSIA(PKOC) Support

※ Specification is subject to change without notice.

規格

- **Supported Interface**
RS232 /Serial TTL 19200,N,8,1
USB 2.0 Full Speed
- **CCID Compliance**
Supports PC/SC
- **Supported Protocols**
ISO14443A, all bit rates : up to 848 Kbps
ISO15693, all modes
Downlink 1 of 4 and 1 of 256
Uplink 6.6/13/26/53 kbps with 1 & 2 sub-carrier
- **Card Compatibilities**
125KHZ EM Format
13.56MHZ
ISO 14443A
MIFARE™ Standard, MIFARE 4k, MIFARE Ultralight, MIFARE Ultralight C, MIFARE DESFireR, MIFARE DESFire EV1, DESFire EV2, DESFire EV3
ISO 14443B
Smartcard ISO14443B, SRI4K, SRI512
ISO 15693
SIC5600, ICODE-SLI, ICODE-SLI-L, ICODE-SLIS
Read paywave and paypass
ISO7816 T=CL
NFC TAG 1~4 supportive
Read ISO18092 Felica & PICOPASS UID
- Ultra small outline 104x45x15.2 mm
- Information Support
Visual C# demonstration Software
Protocol Information
- Low power, low profile for portable designed
- Plug-in fitting for 13.56Mhz / 125KHZ
- 工作模式 200mA @5VDC
- 低功耗模式 0.9mA@ 5VDC(根據不同界面而定)
- 電壓範圍 5~48V
- Firmware Update

特色:

- 頻率：13.56 MHz /125KHZ
- 讀 / 寫 NFC 1~4 TAGs / ISO14443A / B / ISO15693
- 高速資訊傳送
- 0.9mA 低功耗設計
- 抗碰撞
- 同時支援 USB HID / CCID / PC/SC 界面
- 支援 Ibutton Decode 最多可串 5 顆

Standard Configurations:

- MP610---- USB Interface
- MP620---- RS232/Wiegand/1-Wire Interface
- MP625---- RS232/RS485/Wiegand/1-Wire Interface

- ✓ We welcome OEM inquiries
- ✓ Custom device programming is available